Measuring direct vision for truck cabs

Alexander K Epstein, PhD Michael T. Chang November 19, 2019






Advancing transportation innovation for the public good



- Direct vision of truck (and other vehicle) cabs
- Why direct vision? Why now? Why trucks?
- Volpe contribution and future work
- Assembling an advisory group and stakeholders



Direct vision



Direct vision



Transformative improvement

Incremental improvement

Peep window:

Sloped hood:







Cab forward:

Low-entry, high-vision truck cab:






Why direct vision?




faster reaction time through direct vision













Credit: FMCSA

WHY TRUCKS: CRASH CAUSATION (UK)

Accide	ents between HGVs and cyclists	Accidents between HGVs and pedestrians				
No. of accidents	Causation category		No. of accidents	Causation category		
723	Failed to look properly		284	Failed to look properly		
357	Failed to judge other person's path or speed		125	Vehicle blind spot		
321	Passing too close to cyclist		105	Poor turn or manoeuvre		
257	Poor turn or manoeuvre		101	Passing too close to horse rider or pedestrian		
219	Careless, reckless or in a hurry		80	Careless, reckless or in a hurry		
159	Vehicle blind spot		50	Failed to judge other person's path or speed		

- Due to the difficulties in ascertaining the exact cause of an accident after the fact these data must be treated with caution
- However, vision related causal factors account for nearly 37% of all accidents involving a truck and a pedestrian and 33% involving a truck and a cyclist
- This trend was consistent whether at a National level or purely in London.



Direct Vision Standard (DVS)

Alina Tuerk and Vicky Sims Transport for London




EVERY JOURNEY MATTERS

Chan In the Content


Why Now? Direct Vision Standard (DVS)

- TfL world's first Direct Vision Standard for HGVs
- Objective measurement of the 'volume of space' weighted by risk to other road users
- This measurement is converted to a "star rating' from zero (worst) to five (best)

- UNECE to support the minimum 1 STAR definition in all new trucks by 2024 and all trucks on the road by 2028
- An EU impact assessment has shown that this could save 550 lives every year in Europe



Volpe contribution and future work





VIEW Blind Spot Measurement App: DATA COLLECTION







2. Take vehicle measurements

1. Place the height measurement pole & camera stand



Measurements are taken from th pole to the front bumper, from the bumper to the camera lens.

And from the ground to the camera lense

IMAGE PROCESSING



WEB APPLICATION


https://blindspotcalculator.herokuapp.com/

- Upload panoramic photo
- Outputs visibility percentage
- Option to add truck information to database


Add Truck	Get Existing Truck Info					
			VIEW	1		
		Blind Spot	t Calculator for La	arge Trucks		
Choose fi	eld of view ima	ge to upload				
Choose File N						

Instructions


- The image you upload will look warped, that's okay
- You may want to consider cropping your image if the windows do not make up the majority of the photo
- Try to be as accurate as possible
- · You will need the four measurements shown here:



BLIND AND TOTAL VOLUMES




Blind Spot Comparison







Volpe contribution and future work



Stakeholders, awareness and next steps

Is this an issue you were aware of or thinking about?

What other stakeholder agencies or organizations are working in this space? (beyond the table)

What is the path forward to understanding and managing direct vision as an emerging issue?

OA / Office				
FMCSA Technology Division				
FMCSA Vehicle and Roadside Operations Division				
NHTSA HF				
FHWA Safety and Human Factors				
NIOSH Division of Safety Research				
NHTSA VRTC				
NHTSA Electronic Systems Safety				
NHTSA Research				
CVSA				



Thank you

Alexander K Epstein, Ph.D. Michael T. Chang

(617) 494-2539 | <u>alexander.epstein@dot.gov</u> (617) 494-3809 | <u>michael.chang@dot.gov</u>



